



TNR INDUSTRIAL DOORS INC.

SHOP DRAWING, SECTOR

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES	EXT. DETAIL: -
<input type="checkbox"/> - BLUE CURTAIN	<input type="checkbox"/> - N 4X, WALL MOUNTED CONTROL PANEL	- AVAILABLE IN 575/480/460/230 VOLT	LIMITATIONS: MAX. OPENING WIDTH 16', MAX. OPENING HEIGHT 16'
<input type="checkbox"/> - ORANGE CURTAIN	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. _____	- PLUG AND PLAY ELECTRICAL CONNECTIONS	DATE DR'N: NOVEMBER 3, 2008 REVISION: RELEASE
<input type="checkbox"/> - RED CURTAIN	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- ENCLOSED COUNTERWEIGHT SYSTEM	DRAWN BY: HOWARD MULRAIN DRAWING No.: D-609-0002
<input type="checkbox"/> - VISION PANEL IN P1 (MIN. HEIGHT = 6' 6")	<input type="checkbox"/> - THRU-BEAM PHOTOSWITCH, QTY. _____	- EMERGENCY RELEASE MECHANISM	ELECTRICAL CRITERIA:
<input type="checkbox"/> - VISION PANEL IN P2 (MIN. HEIGHT = 9' 6")	<input type="checkbox"/> - PULL CORDS, QTY. _____	- FAILSAFE REVERSING EDGE	STANDARD CONTROL PANEL NEMA/EEMAC 4
<input type="checkbox"/> - VISION PANEL IN P3 (MIN. HEIGHT = 12' 6")	<input type="checkbox"/> - AUXILLARY, DRY ELECTRICAL CONTACT	- TWO (2) FAILSAFE PHOTO CELLS	PRIMARY POWER SUPPLY: _____ Volts, Single Phase, 60 Hertz
<input type="checkbox"/> - BOTTOM BAR LOOP	<input type="checkbox"/> - ELECTRICAL INTERLOCK	- KNOCK AWAY BOTTOM PANEL	END USER:
<input type="checkbox"/> -	<input type="checkbox"/> -	-	DEALER:
<input type="checkbox"/> - AUX. EMERGENCY RELEASE MECHANISM	<input type="checkbox"/> -	-	DOOR SIZE: _____ SERIAL No.: -