



IMPORTANT: SEE DRAWING D-600-0039 FOR FRAMING REQUIREMENTS

** CLEARANCE DIMENSION IS 14 1/2" FOR OPTIONAL CONCRETE MOUNT CONFIGURATION
 *** OPTIONAL HOODS REQUIRE 14" & 17" SIDEROOM, 52" HEADROOM AND 48" OPERATOR PROTRUSION

TNR INDUSTRIAL DOORS INC.

SHOP DRAWING, MODEL HDXL 8, LEFT HAND

EXT. DETAIL: DOOR MT. OPERATOR & C'BAL SPRINGS, 2 PC. IDLER

LIMITATIONS: 30' < O.W. <= 35' & 30' < O.H. <= 35' OR 35' < O.W. <= 40' & 25' < O.H. <= 35'

DATE DR'N: AUG. 4, 2006 REVISION: REL

DRAWN BY: BRYAN AWREY DRAWING No.: D-600-0037

ELECTRICAL CRITERIA:

CONTROL PANEL NEMA/EEMAC 4 STD. OR _____

PRIMARY POWER SUPPLY: _____ Volts, 3 Phase, 60 Hertz

OPERATOR CRITERIA: HG, HIGH EFFICIENCY HELICAL GEAR

LIMIT BOX NEMA/EEMAC 4 STD. OR _____

____ HP, DOOR SPEED: OPEN & CLOSE @ _____ ips

END USER:

DEALER:

DOOR SIZE: SERIAL No.:

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES
<input type="checkbox"/> - 100,000 CYCLE C'BAL SPRINGS	<input type="checkbox"/> - RELAY LOGIC CONTROLS	- SPEED AS SHOWN
<input type="checkbox"/> - GUIDE GUARDS	<input type="checkbox"/> - FUSED DISCONNECT	- NEMA 4, WALL MOUNTED CONTROL PANEL
<input type="checkbox"/> - *** GALV. DOOR HOODS	<input type="checkbox"/> - LOOP DETECTOR	- NEMA 4 LIMIT BOX ON OPERATOR
<input type="checkbox"/> - 16" x 16" WINDOWS, QTY. _____	<input type="checkbox"/> - WIRELESS RECEIVER	- 50,000 CYCLE COUNTERBALANCE SPRINGS
<input type="checkbox"/> - BLUE EPDM CURTAIN	<input type="checkbox"/> - WIRELESS TRANSMITTER, QTY. _____	- REVERSING EDGE
<input type="checkbox"/> - GRAY EPDM CURTAIN	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. _____	- THRU-BEAM PHOTOEYE
<input type="checkbox"/> -	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- 5" HIGH, BLACK EPDM RUBBER LOOP
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. _____	- KNOCK-AWAY STYLE BOTTOM BAR
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- NEWGEN GUIDE AND CURTAIN LOK SYSTEM
<input type="checkbox"/> -	<input type="checkbox"/> - CONSTANT PRESSURE CLOSE	- 90 MPH WINDLOAD RATING
<input type="checkbox"/> -	<input type="checkbox"/> -	- PROGRAMMABLE CONTROLLER
<input type="checkbox"/> -	<input type="checkbox"/> -	-